

Combining frequency domain reflectometry and visible and near infrared spectroscopy for assessment of soil bulk density

Raed A. Al-Asadi, Abdul M. Mouazen*

^a Natural Soil Resources Institute, Environmental Science and Technology Department,
Cranfield University, Bedfordshire, MK43 0AL, United Kingdom

E-mail of corresponding author: a.mouazen@cranfield.ac.uk

Abstract

This paper introduces a new approach for the assessment of soil bulk density (BD), which relies on an existed model to predict BD as a function of a visible and near infrared spectroscopy (vis-NIRS) measured gravimetric moisture content (ω) and a frequency domain reflectometry (FDR) measured volumetric moisture content (θ_v). A total of 1013 soil samples collected from England and Wales, from 32 arable and grassland fields with different soil types were measured with a vis-NIR spectrophotometer (LabSpec®Pro Near Infrared Analyzer, Analytical Spectral Devices, Inc, USA) after *in situ* measurement with a ThetaProbe FDR (Delta-T Device Ltd). Two calibration methods of the vis-NIRS were tested, namely, partial least squares regression (PLSR) and artificial neural network (ANN). ThetaProbe calibration was performed with traditional methods and ANN. ANN analyses were based on a single input or multiple input variables (data fusion). During ANN - data fusion analysis, vis-NIRS spectra and ThetaProbe output voltage (V) were fused in one matrix with or without laboratory measured texture fractions and organic matter content (OM). For the vis-NIRS and ThetaProbe traditional calibration, samples were divided into calibration (75 %) and prediction (25 %) sets, whereas for the ANN analysis these were divided into calibration (65%), test (10%) and independent validation (25%) sets. Results

proved that high measurement accuracy can be obtained for ω and θ_v with PLSR and the best performing traditional calibration method of the ThetaProbe with R^2 values of 0.91 and 0.97, and root mean square error of prediction (RMSEp) of 0.027 g g^{-1} and $0.019 \text{ cm}^3 \text{ cm}^{-3}$, respectively. However, the ANN – data fusion resulted in improved accuracy ($R^2 = 0.98$ and RMSEp = 0.014 g g^{-1} and $0.015 \text{ cm}^3 \text{ cm}^{-3}$, respectively). This data fusion approach led to the best accuracy for BD assessment when vis-NIRS spectra and ThetaProbe V only were used as input data ($R^2 = 0.81$ and RMSEp = 0.095 g cm^{-3}). It can be concluded that BD can be measured by combining the vis-NIRS and FDR techniques based on ANN-data fusion approach.

Keywords: Bulk density, multi-sensor, data fusion, vis-NIR spectroscopy, FDR.

1. Introduction

Forest, arable and grasslands are important natural resources, which have been subjected to artificial and natural compression stresses through the ages. Heavy agriculture machinery, intensive use of the arable lands and livestock impact on grasslands during the wet soil conditions, are among the major factors causing compression stresses, which lead to soil compaction (Vrindts et al., 2005). Soil compaction is normally associated with damage of the soil structure, deterioration of physical and hydraulic properties and creation of unfavourable conditions for plant root system. Compacted soils demand large amount of fertilisers, in order to substitute the small volume available for plant roots, which might cause contamination hazardous of the ground water by the deep percolation or the run off to the surface water (Soane and van Ouwerkerk, 1995). Highly compacted soils can be considerably of low productivity and require more mechanical power for soil preparations. Among other parameters used to assess soil compaction, bulk density (BD) that is the closer packing of

solid particles or the reduction in porosity is a widely used parameter (Grossman, 1981; Bardy, 1984; Singh et al., 1992; Wuest et al., 2009). However, BD might be considered as a sing of soil compaction, as it does not necessarily reflect soil functioning (e.g. air and water movement) (Quraishi and Mouazen, 2013a). Other parameters e.g. saturated hydraulic conductivity and infiltration rate are more closely related to soil compaction (Fleige and Horn, 2000), as compared to BD. However, in comparison with the latter parameters, assessment of BD with a portable system is possible (Quraishi and Mouazen, 2013a) and enables faster, easier and more cost effective data acquisition, which is particularly useful for precision agriculture applications.

The most common traditional method for BD measurement is the core sampling method (e.g. Kopecki ring), which is laborious, time consuming, expensive and difficult to conduct under dry soil conditions (Quraishi and Mouazen, 2013b). This is the reason why penetrometers to measure soil penetration resistance, known as cone index is widely used to map the variation in soil compaction with depth (Sun et al., 2011). However, Mouazen and Ramon (2006) explained that penetration resistance is simultaneously affected by moisture content, texture, BD and organic matter content (OM). Therefore, a new method to measure BD is required that should be fast, easy, cost effective and do not need an expert operator.

For years, visible and near infrared spectroscopy (vis-NIRS) has provided a proven and versatile analytical method for soil analyses (Viscarra Rossel & McBratney, 1998; Shepherd & Walsh, 2002; Clark et al, 2005; Mouazen et al, 2010; Stenberg et al., 2010). It is fast measurement technique, non-destructive and cost effective (Mouazen et al., 2005). It was successfully used to measure gravimetric moisture content (ω) under laboratory non-mobile measurement conditions (Dalal and Henry, 1986; Slaughter et al., 2001; Lobell and Anser, 2002; Mouazen et al., 2006a) and on-line mobile conditions (Mouazen et al., 2005). These

successful applications were attributed to the strong influence of O-H bond on vis-NIR spectra of soils (Kuang et al., 2012; Stenberg et al., 2010).

The measurement of dielectric constant (K) based on frequency domain reflectometry (FDR) is a popular technique for the measurement of soil volumetric moisture content (θ_v) (Topp et al., 1980; Miller and Gaskin, 1997; Robinson et al., 1999). This is due to the fact that K of the water (~ 80) is significantly greater than that of the dry soil matrix materials (~ 4) and of the air (~ 1). ThetaProbe (Delta-T Devices Ltd., 1999) was reported to be capable to measure soil θ_v with $\pm 0.01 \text{ m}^3 \text{ m}^{-3}$ accuracy after a single two-point gravimetric calibration, although, $\pm 0.05 \text{ m}^3 \text{ m}^{-3}$ accuracy can be achieved when generalised calibration by the manufacturer is applied (Foley and Harris, 2007; Kaleita et al., 2005; Jones et al., 2002; Walker et al., 2004).

Multiple sensor and data fusion is being introduced as a new concept in proximal soil sensing (Kuang et al., 2012). Data fusion is an important tool that may improve the performance of a detecting system while various integrated sensors are available (Mahmood et al., 2009). Despite the fact that this is a new concept, several studies were reported for non-mobile (Hummel et al., 2004; Quraishi and Mouazen, 2013b) and mobile (Glancey et al., 1989; Mouazen et al., 2003; Adamchuk et al., 2004; Mouazen et al., 2005; Mouazen and Ramon, 2006; Naderi-Boldaji et al., 2012; Quraishi and Mouazen, 2013c) measurement conditions. Quraishi and Mouazen (2013b) reported a data fusion approach of BD assessment, based on the fusion of data on ω , OM and clay content (C), measured with a vis-NIR spectrophotometer and penetration resistance measured with a penetrometer. However, a large number of variables e.g. ω , OM, C and penetration resistance is needed as input for the artificial neural network (ANN) to predict BD is required. The accumulated error of vis-NIR measurement of ω , OM and C would sum up to a considerable error of BD assessment. Therefore, a simpler approach is needed that is based on a fusion of fewer input variables (e.g. ω and θ_v), where error in BD assessment is small.

The aim of the paper is to introduce a new approach for BD assessment to be adopted for precision agriculture applications, which is based on a multi-sensor and data fusion approach. It relays on combining the vis-NIRS measurement of ω and ThetaProbe measurement of θ_v , which are substituted into an existed model to predict BD.

2. Materials and methods

2.1. Experimental sites and soil samples

A total of 1013 undisturbed soil samples were collected, at the same time of the field measurement, from 32 fields in seven locations in England e.g. Silsoe and Wilstead in Bedfordshire, Haversham and Gayhurst in Buckinghamshire, Flawborough in Nottinghamshire, Nafferton and Morpeth in Northumberland and from one location in Wales e.g. Brecon. They have been collected from the top layer of 10-20 cm between May, 2011 and December, 2012. Detailed information about these fields is shown in Table 1. These fields were of a wide range of soil texture (Fig. 1), moisture content, OM and BD and were under different land use (Tables 1 and 2). This wide variability is advantage to allow testing the applicability of the new measurement system of BD under different field conditions. Soil cores were collected by a rigid ploy vinyl chloride (PVC) cylinder of 60 mm height and 50 mm in diameter, and were transferred to the laboratory for further analysis. All soil cores were kept in the PVC cylinders sealed in plastic pages to prevent moisture losing. They stored at 4 °C from the time of sampling until the time of analysis.

2.2. Laboratory analysis

Soil BD, θ_v , ω for all 1013 samples were measured by oven drying of samples at 105°C for 24 h (British Standards, 2007). Particle size distribution (PSD) and OM were measured for average field samples. The PSD was measured by sieving and sedimentation method (British

Standards, 1998). Soil OM was measured with a TrusSpecCNS spectrometer (LECO Corporation, St. Joseph, MI, USA), using the Dumas combustion method (British Standards, 2000). Results of laboratory analyses are shown in Tables 1 and 2.

2.3. Soil bulk density estimation

The following relationship exists between BD, ω and θ_v (Wijaya et al., 2004):

$$BD = \theta_v / \omega \quad (1)$$

Where: BD is the soil bulk density in g cm^{-3} , θ_v is the volumetric moisture content in $\text{cm}^3 \text{ cm}^{-3}$ and ω is the gravimetric moisture content in g g^{-1} .

The hypothesis of this study is that by substituting θ_v measured with a ThetaProbe and ω measured with a vis-NIR spectrophotometer into Eqn (1), BD can be derived with acceptable accuracy as compared to the oven drying method of soil samples at 105 °C for 24 h. This hypothesis will be tested in this study.

2.4. ThetaProbe and visible and near infrared spectroscopy

A ThetaProbe and a vis-NIR spectrophotometer were used to measure θ_v and ω , respectively.

A detailed description of the measurement is provided in the following subsections.

2.4.1. ThetaProbe description

ThetaProbe (Delta-T Devices Ltd., 1999) is the commercial name of dielectric probe to measure θ_v . It has been developed jointly by the Macaulay Land Use Research Institute, Scotland and Delta-T Devices Ltd, Cambridge. ThetaProbe consists of waterproof housing, which contains electronic circuit attached to it at one end, and four parallel stainless steel rods of 60 mm long and 3 mm in diameter, to be inserted into the soil and at the other end

input/output cable (Fig. 2). The electronic circuit generates and emits electromagnetic signal of sinusoidal shape, which is applied to an internal transmission line to the array of four rods. The impedance of this array varies according to the impedance of the soil, which has two components, namely, the apparent dielectric constant (K) and the ionic conductivity. A 100 MHz of frequency was chosen in order to minimise the effect of ionic conductivity, so that changes in the transmission line impedance dependent almost solely on the soil's apparent K . Water content determines K of the soil, as K of the water (~81) is much higher than K of the soil (3 to 5) and that of the air (1). The traveling electromagnetic wave through the soil mass will cause a voltage standing wave to be set up from the interference of the emitted signal and its reflected component. By measuring this voltage amplitude, K of the soil can be obtained and thus θ_v . More details can be found in Gaskin in Miler (1996) and Miller and Gaskin (1997). Kaleita et al. (2005) studied the effect of soil temperature on laboratory calibration of ThetaProbe, and found insignificantly differences in the accuracy for a temperature range of 10 to 40 °C. Insignificant effect of soil salinity in the range of 250 - 2000 mS m⁻¹ was confirmed by the ThetaProbe manufacturer (Delta-T Devices Ltd., 1999).

2.4.2. ThetaProbe calibration and validation

Three ThetaProbe readings were recorded *in situ* from the same spot (e.g. 50 cm in diameter), where the soil core was collected. Additional reading was also recorded from the soil core itself. These four readings were averaged in one final reading. In this study, five methods for the calibration of ThetaProbe were tested, namely, manufacturer (M), specific soil calibration (SSC), general formula (GF) (Topp et al. 1980), and ThetaProbe output voltage (OV) and ANN. The input for all calibration was the readout of the ThetaProbe only. In the following subsections, the first four methods are explained, whereas, for simplicity, ANN is explained in a later section.

2.4.2.1. Manufacturer calibration method (M)

The general calibration by the manufacturer of the device is a pre-set programme at ThetaProbe digital moisture meter type (HH2), which provides instant readout of θ_v and also V . It comprises two calibration options for mineral and organic soils (Delta-T Devices Ltd., 1999). It is based on the following third order relationship between K and V :

$$\sqrt{K} = 1.07 + 6.4V - 6.4V^2 + 4.7V^3 \quad (2)$$

Where \sqrt{K} is the square root of the dielectric constant and V is the output voltage reading of the ThetaProbe.

By substituting \sqrt{K} into the following equations, θ_v can be calculated for mineral and organic soils, respectively:

$$\theta_v = \frac{\sqrt{K}-1.6}{8.4} \quad (3)$$

$$\theta_v = \frac{\sqrt{K}-1.3}{7.7} \quad (4)$$

2.4.2.2. Specific soil calibration method (SSC)

This method relies on Eqn. (1), but is used for specific soil types. To calculate θ_v for a specific soil, the following linear relationship between \sqrt{K} and θ_v was established (Delta-T Devices Ltd., 1999):

$$\theta_v = \frac{\sqrt{K}-a_0}{a_1} \quad (5)$$

Where a_1 and a_0 are coefficients for wet and dry soil sample, respectively. a_0 is considered equal to $\sqrt{K_0}$ (Gaskin and Miller, 1996). However, a_1 is calculated from the following equation:

$$a_1 = \frac{\sqrt{K_1} - \sqrt{K_0}}{\theta_{vt}} \quad (6)$$

$\sqrt{K_1}$ is the square root of the dielectric constant of the wet undisturbed soil sample, $\sqrt{K_0}$ is the square root of the dielectric constant of the dried undisturbed soil sample, both $\sqrt{K_1}$ and $\sqrt{K_0}$ were measured using Eqn. (2), θ_{vt} is measured volumetric moisture content by oven drying of samples for 105 °C for 24 h.

2.4.2.3. General formula calibration method (GF)

This method relies on the concept that K can be measured from the standing voltage of the soil matrix and thus indicates θ_v . Topp et al., (1980) established the universal equation to express the relation between θ_v and K of many soil types, collected from all over the world, which is written as follows:

$$\theta_v = -0.053 + 0.0292K - 0.00055K^2 + 0.0000043K^3 \quad (7)$$

The K value is derived based on average measured V , which is substituted into Eqn. 7. to calculate θ_v .

2.4.2.4. Output voltage calibration method (OV)

In this method a direct relationship between V and θ_v was established based on *in situ* measurement of ThetaProbe of soils collected in the current study. The average spot

ThetaProbe output readings of 1013 samples were divided into two sets, namely, calibration (75%) and independent validation set (25%). The former was used to generate the relationship between θ_v and V , whereas the latter was used to validate the calibration equation developed.

2.5. Visible and near infrared spectrophotometer calibration and validation

The fresh, remoulded soil samples were scanned in the laboratory in three replicates, by a LabSpec vis-NIR portable spectrophotometer (LabSpec Pro Near Infrared Analyzer, Analytical Spectral Devices, Inc, USA) (ASDi). The diffuse reflected light from the top 2-3 mm layer of 117.75 cm³ cylindrical samples was collected. The spectrophotometer has one Si array (350 – 1000 nm) and two Peltier cooled InGaAs detectors (1000 –1800 nm and 1800 – 2500 nm). Spectra sampling interval of the instrument was 1 nm across the entire spectra range. However, the spectral resolution was 3 nm at 700 nm and 10 nm at 1400 and 2100 nm. A high intensity probe with a light source built in of a quartz-halogen bulb of 3000 K° light was used. The detection fibres were gathered in the high intensity probe enclosing 35° angle. Before scanning, only large plant residues, debris and stones were removed from the fresh samples (Mouazen et al., 2005). Different amounts of non-sieved soil according to different textures were packed in Petri dishes of a 1.0 cm height by 3.6 cm in diameter. Soil in a Petri dish was mixed properly and a gentle pressure was applied on the surface with a spatula to generate levelled and smooth surface to ensure a maximum diffuse reflection and thus a good signal-to-noise ratio (Mouazen et al., 2007). Before the soil samples were scanned and at intervals of 30 min, a white reference Spectralon disc was scanned. Three readings were collected from each soil sample and these were averaged in one spectrum to be used for spectra pre-treatment and model establishment.

2.5.1. Spectra pre-treatment and establishment of calibration model

Spectra pre-treatment aimed to reduce spurious peaks that do not contain physical or chemical information and to correct physical scatter effects. Soil spectra range was first reduced to 500– 2200 nm, to eliminate noise at both edges and to enhance calibration accuracy for ω measurement (Mouazen et al., 2005). After noise cut, spectra were reduced by averaging 10 successive wavelengths. Maximum normalisation was followed, which is typically used to get all data to approximately the same scale, or to get a more even distribution of the variances and the average values. The maximum normalisation is a normalisation that “polarizes” the spectra. The peaks of all spectra with positive values were scaled to + 1, while spectra with negative values were scaled to – 1. Since soil spectra have maximum positive values, the peaks of these spectra were scaled to + 1 (Mouazen et al., 2005). The maximum normalisation led to better results for ω measurement, compared to other pre-treatment options tested. Spectra were then subjected to Savitzky–Golay first derivation transformation (Martens and Naes, 1989). This method enables to compute the first or higher order derivatives, including a smoothing factor, which determines how many adjacent variables will be used to estimate the polynomial approximation used for derivatives. A second order polynomial approximation was selected. A 2:2 smoothing was carried out after the first derivative to decrease noise from the measured spectra. All pre-treatment steps were carried out using Unscrambler 7.8 software (Camo Inc.; Oslo, Norway). The entire 1013 soil spectra were divided into calibration (75%) and independent validation (25%) sets. Partial least squares regression (PLSR) was implemented using the calibration set to relate the variation in one response variable (e.g. ω) to the variation in multi-spectra wavelengths, using Unscrambler 7.8 software (Camo Inc.; Oslo, Norway). It is a bilinear modelling method where information in the original x data is projected onto a small number of underlying (“latent”) variables called PLS components. The y data are actively used in

estimating the “latent” variables to ensure that the first components are those that are most relevant for predicting the y variables. Interpretation of the relationship between x data and y data is then simplified as this relationship is concentrated on the smallest possible number of components. More detailed information about the PLSR can be found in Martens and Naes (1989).

To evaluate model accuracy for the measurement of ω , the root mean square error of prediction ($RMSEP$) of the independent validation set was considered. The coefficient of determination (R^2) and residual prediction deviation (RPD), which is the ratio of standard deviation (SD) values of the laboratory measured ω divided by $RMSEP$ of the independent validation set were also considered to evaluate the performance of calibration models (Mouazen et al., 2010). Mouazen et al. (2006b) proposed the following classes of the RPD values: an RPD value below 1.5 indicates poor model predictions and that such a value could not be useful; an RPD value between 1.5 and 2.0 indicates a possibility of distinguishing between large and small values, while a value between 2.0 and 2.5 makes approximate quantitative predictions possible. For RPD values between 2.5 and 3.0 and above 3.0, the prediction is classified as good and excellent, respectively. This classification system of RPD was adopted in this study. Generally, a good model performance would have high R^2 and RPD values, and a small value of $RMSEP$.

2.6. Data fusion and modelling

Methods adopted in sections 2.2. and 2.3. for the measurement of θ_v and ω , respectively, were based solely on output signal of ThetaProbe or vis-NIRS, respectively. In this section, the measurement of θ_v and ω is based on fusion of output data from both sensing techniques (V and spectra) with or without data obtained from laboratory analysis on sand (S in %), silt (SL in %), C in % and OM in %. However, in order to compare with other data fusion

models, input data of V or soil spectra were used for the measurement of θ_v and ω , respectively.

One of the tools available for data fusion is the ANN. Neural networks are simplified models of the biological structure of human brains (Günaydin, 2009). There are three main layers in the ANN structure, namely, a set of input nodes, one or more layers of hidden nodes and a set of output nodes. In this study, different number of nodes was used in each layer depending on the input data used (Fig. 3). For instance, the number of nodes of the hidden layer for θ_v based on V only was two layers (Table 3). Seven ANN analyses were performed to develop different models, according to the different input variables used (Table 3). The output layers for different combinations were θ_v or ω , or both. All the modelling cases were developed with Statistica software (StatSoft, USA, 2011). The powerful second order Broyden–Fletcher–Goldfarb–Shanno (BFGS) training algorithms, with different transfer functions used for hidden and output layers were used, as detailed in Table 3. The transfer functions included hyperbolic tangent (Tanh), logarithmic (Log) and exponential (Exp). The number of neurons in the hidden layer is established by training several networks with different number of hidden neurons, and comparing the predicted with measured values. In this study, a hidden layer with five neurons showed the best results. Data for the entire 1013 soil samples were divided into training set (65%), test set (10%) and independent validation set (25%). All the texture classes were included in the three sets so that the resulted models are valid for all textures.

The measured values of ω and θ_v obtained, respectively, based either on the traditional calibration of the vis-NIRS and ThetaProbe or on the ANN analyses were used to predict BD using Eqn. (1). The performance of the developed models was evaluated by means of R^2 and RMSEp.

3. Results and discussion

3.1. Accuracy of ThetaProbe measurement for volumetric moisture content

Table 4 shows the results of the measurement accuracy of θ_v with the ThetaProbe against the oven drying method using M, SSC, GF, OV and ANN calibration models with one input parameter (e.g. output voltage V). Results suggest that the ThetaProbe is capable to measure θ_v with high accuracy even with the M calibration method, without the need for additional calibration. However, slight differences can be observed between these methods. With the M method, the measured values of θ_v overestimate the oven drying measured values. Working with M method, Robinson et al. (1999) and Kaleita et al. (2005) observed similar overestimation for a group of soil samples across a full range of moisture content. Both research groups indicated that the accuracy of the ThetaProbe declined with moisture content, which is a similar trend observed in the current study. The scatter plot of the ThetaProbe-M predicted versus oven drying measured θ_v illustrates intercept with x axis with a value of $1.12 \text{ cm}^3 \text{ cm}^{-3}$, indicating overestimation of the M model (Fig. 4). The SSC calibration method performs as equal as that of the M method. However, the GF calibration method provide an improved measurement accuracy ($R^2 = 0.96$ and $\text{RMSEp} = 0.020 \text{ cm}^3 \text{ cm}^{-3}$) (Table 4). The RMSEp obtained with these three methods (e.g. M, SSC and GF) is still larger than $0.01 \text{ m}^3 \text{ m}^{-3}$, which contradicts the instruction provided by the ThetaProbe's manufacturer. The OV calibration method leads to further improvement ($R^2 = 0.97$ and $\text{RMSEp} = 0.019 \text{ cm}^3 \text{ cm}^{-3}$), as compared to the M, SSC and GF methods. ANN analysis with one input (e.g. V) does not perform as good as ($R^2 = 0.96$ and $\text{RMSEp} = 0.021 \text{ cm}^3 \text{ cm}^{-3}$) the OV method. However, the ANN performance is the second best after the OV method. The worst performing methods are the SSC and M with the largest RMSEp values of 0.026 and 0.025 $\text{cm}^3 \text{ cm}^{-3}$, respectively. Cosh et al. (2005) compared the performance of the M and SSC

methods using 180 samples collected from arable and grassland sites with a wide range of soil texture. They reported a smaller RMSEp value with SSC ($0.040 \text{ cm}^3 \text{ cm}^{-3}$), as compared to M ($0.053 \text{ cm}^3 \text{ cm}^{-3}$). This RMSEp range is overall larger than that obtained in the current study, although we accounted for different textures, OM and land use (Table 4).

The ANN calibration method based on data fusion generally provides better measurement of θ_v , with best results obtained when both V and vis-NIR spectra were used as input data (Table 3) for training ($R^2 = 0.98$ and $\text{RMSEp} = 0.015 \text{ cm}^3 \text{ cm}^{-3}$), in comparison with the M, GF, SSC, OV and ANN-V models. Furthermore, this ANN-data fusion analysis with V and spectra only performs the best among other ANN data-fusion analyses, where texture fractions and OM were used as input together with V and spectra (Table 4). In addition to the fact that the ANN – data fusion model results in the best measurement accuracy of θ_v , a shorter time was needed to conduct ANN calibration-prediction, as compared to the single input modelling methods. This technique requires only V and soil spectra to be used as input data, which are anyway measured by ThetaProbe and vis-NIRS, respectively.

After the ANN – data fusion model, the OV calibration model with one input variable (e.g. V) can be ranked as the second best predicting of θ_v (Table 4), when validated with the independent validation set. By using 75% (759 samples) of the total 1013 soil samples, the following 2nd order polynomial equation is established with OV method (Fig. 5):

$$\theta_v = 0.52V^2 - 0.161V + 0.141 \quad (8)$$

Equation (8) is based on wide variations in soil type, moisture content, OM and land use (Table 1) of UK soils. Therefore, it is an improved regression equation as compared, for example with that reported by Kaleita et al. (2005), who attempted to relate θ_v with K , using

a smaller number of 100 samples only. Their regression models resulted in R^2 values of 0.85 and 0.77 for the laboratory and *in situ* experiments, respectively. The GF regression equation of Topp et al. (1980) based on soil samples collected from all over the world, provided an adequate estimation of θ_v in the range $<0.5 \text{ cm}^3 \text{ cm}^{-3}$, which covers the entire range of interest in most mineral soils, with a RMSEp of $0.013 \text{ cm}^3 \text{ cm}^{-3}$. Jones et al. (2002) reported a shortcoming of GF method for θ_v exceeding $0.5 \text{ cm}^3 \text{ cm}^{-3}$ in organic or mineral soils with high OM or C content. The GF regression equation results in a slightly smaller accuracy (RMSEp = $0.020 \text{ cm}^3 \text{ cm}^{-3}$), as compared to that (RMSEp = $0.020 \text{ cm}^3 \text{ cm}^{-3}$) obtained with Eqn. (8), as shown in Table 4.

3.2. Accuracy of visible and near infrared spectroscopy for gravimetric moisture content measurement

When the vis-NIR spectra only used as input data, a smaller measurement accuracy of ω was obtained with the PLSR model ($R^2 = 0.91$ and RMSEp = 0.027 g g^{-1}), as compared to the ANN model ($R^2 = 0.95$ and RMSEp = 0.020 g g^{-1}) (Table 4). This is expected results, as ANN has been proved to over-perform PLSR for the measurement of soil properties with vis-NIRS (Khalilmoghadam et al., 2009; Mouazen et al., 2010; Viscarra Rossel and Behrens, 2010; Quraishi and Mouazen, 2013b). However, this is a clear contradict to the measurement of θ_v . ANN – data fusion based analysis results in much improved measurement performance of ω , as compared to PLSR technique. Furthermore, ANN – data fusion modelling based on V and spectra, over-performs ($R^2 = 0.98$ and RMSEp = 0.014 g g^{-1}) all other ANN – data fusion analyses based not only on V and spectra only, but laboratory measured texture fractions and OM (Table 4). After ANN – data fusion model based on V and spectra, the best second performing techniques are those based either on the fusion of V , spectra and OM or V , spectra and C ($R^2 = 0.96$ and RMSEp = 0.018 g g^{-1}).

High correlation between ANN – data fusion (e.g. V and soil spectra) measured and oven drying measured ω can be observed in Fig. (6B). This correlation is much improved as compared to that after PLSR (Fig. 6A), which exhibits non-linear behaviour. Since ANN was reported to solve problems with non-linear behaviours such as that shown in Fig. (6A) (Mouazen et al., 2010; Viscarra Rossel and Behrins, 2010), this non-linear behaviour disappeared in Fig. (6B) after ANN – data fusion modelling. The ANN – data fusion results in a RPD value of 4.45 for the independent validation set, which can be classified as excellent measurement performance according to Mouazen et al. (2006b), although the PLSR also results in an excellent but smaller RPD value of 3.57. Mouazen et al., (2006a) stated that the performance of vis-NIRS-PLSR to predict ω is influenced by the scale of modelling. They reported a lower validation accuracy for a sample set collected from multiple fields in Belgium and northern France ($R^2 = 0.91$ and RPD = 3.22), as compared to that of a single-field sample set ($R^2 = 0.97$ and RPD = 5.26). The accuracy of measurement obtained in the current study with both PLSR and ANN – data fusion for a sample set collected from 32 fields in the UK is higher than that reported by Mouazen et al. (2006a), which is encouraging result to suggest using the current ω models for BD assessment. Likewise for θ_v measurement, ANN – data fusion technique provides the best ω measurement performance, and requires the same input of V and soil spectra only (Table 4).

3.3. Bulk density assessment

Having ω and θ_v measured accurately, respectively with the vis-NIRS and ThetaProbe, they are substituted in Eqn. (1) to derive BD. The accuracy of BD assessment with a single input variable (e.g. V or soil spectra) or with multiple input variables (e.g. V , soil spectra, C, S, SL and OM) (Table 3) is discussed in the following sections.

3.3.1 Accuracy of bulk density assessment with a single input variable

Under this BD modelling category, ω is measured based on vis-NIR spectra - PLSR, whereas θ_v is measured based on V only and by means of the five calibration techniques of ThetaProbe discussed above. Generally, the BD assessment in this category is not encouraging ($R^2 = 0.23 - 0.53$ and $\text{RMSEp} = 0.160 - 0.190 \text{ g cm}^{-3}$). The best assessment is obtained with ANN - moisture content model ($R^2 = 0.69$ and $\text{RMSEp} = 0.122 \text{ g cm}^{-3}$), however, this is still with a relatively high RMSEp (Table 4). Figure 7A illustrates the scatter plots of estimated BD with ANN – single input variable moisture content models versus oven drying measured BD. This is still valuable results, as the analysis is capable to predict BD of soils with a wide range of BD variation between 1.0 and 2.0 g cm^{-3} . The intercept of the linear regression equation reveals that the new system over-estimates BD, which might be attributed to the relatively low accuracy of the vis-NIRS for the measurement of ω , as compared to the ThetaProbe for the measurement of θ_v .

3.3.2 Accuracy of bulk density assessment with multiple input variables (data fusion)

Under this modelling category, both ω and θ_v are predicted with ANN based on different combinations of input variables of vis-NIR spectra, V , S , SL , C and OM (Table 3). Generally, as for the measurement performance of ω and θ_v , the assessment of BD (using Eqn. 1) with ANN – data fusion techniques ($R^2 = 0.65 - 0.81$ and $\text{RMSEp} = 0.127 - 0.095 \text{ g cm}^{-3}$) over-performs the corresponding assessments obtained with the single input variable methods ($R^2 = 0.23 - 0.53$ and $\text{RMSEp} = 0.160 - 0.187 \text{ g cm}^{-3}$) (Table 4). These results are in agreement with those reported by Quraishi and Mouazen (2013b). Although high assessment accuracy of BD is obtained with different ω and θ_v models of ANN – data fusion with different combination of input variables, the accuracy increases with the decrease in the number of input variable used for ω and θ_v analyses. This trend is clearly illustrated by the increase in

RMSEp values with the number of input variables used during ANN analyses (Fig. 8C) of the independent validation set. However, R^2 values decrease with the increase in the number of input variable (Fig. 9). This trend can be attributed to a similar trend observed for θ_v (Figs. 8A and 9) and ω (Figs. 8B and 9). One exception is for the ANN model based on V, spectra, C and OM input variables, for which smaller accuracy can be observed, as compared to those obtained with a larger number of input variables (Figs. 8 & 9). Furthermore, ANN – data fusion model with V, Spec and C is less performing, as compared to that with V, Spectra and OM (Figs. 8 & 9). Among all models, the ANN - data fusion with V and soil spectra only used as input variables for the measurement of ω and θ_v performs the best for the assessment of BD using Eqn. (1) ($R^2 = 0.81$ and $\text{RMSEp} = 0.095 \text{ g cm}^{-3}$). This is mainly attributed to a much larger improvement in ω measurement, as compared to θ_v (Table 4), when ANN is used. This model provides useful information about field BD with small RMSEp, to recommend practical application of the new proposed system of combining vis-NIRS and FDR for the assessment of BD.

4. Conclusions

The visible and near infrared spectroscopy (vis-NIRS) for the measurement of the gravimetric moisture content (ω) was combined with the ThetaProbe for the measurement of the volumetric moisture content (θ_v) for *in situ* assessment of soil bulk density (BD). From the results obtained for 32 fields in the UK with different texture, organic matter, moisture contents, and land use, the following conclusions were drawn:

- 1- Soil BD can be measured with the proposed new approach by substituting the vis-NIR measured ω and the ThetaProbe predicted θ_v into an existed BD model with a high accuracy.
- 2- The accuracy of BD assessment depends on the measurement accuracy of ω and θ_v . The highest accuracy ($R^2 = 0.81$ and $\text{RMSEp} = 0.095 \text{ g cm}^{-3}$) was based on ω and θ_v values

predicted with artificial neural network (ANN) – data fusion models with ThetaProbe output voltage (V) and vis-NIRS spectra used as input variables.

2- The performance of the BD model based on ANN – data fusion approach deteriorated with the number of input variables used to predict ω and θ_v .

A further research is being undertaken to improve the calibration of the ANN models, by understanding and quantifying the effects of moisture, texture and land use on the measurement accuracy. Investigation is being undertaken to develop a portable system by implementing the results achieved in the current work.

5. Acknowledgments

Authors acknowledge the financial support of the Engineering and Physical Science Research Council and The Douglas Bomford trust.

6. References

Adamchuk, V.I., Morgan, M.T., Sumali, H., 2001. Application of a strain gauge array to estimate soil mechanical impedance on-the-go. Transactions of the ASAE, 44(6), 1377–1383.

Bardy, N.C., 1984. The Nature and Properties of Soils, 9th ed. MacMillan Publishing Co., New York, USA.

British Standards, 1998. Soil quality: BS 7755: Section 5.4: 1998. Part 5: Physical methods. Section 5.4: Determination of particle size distribution in mineral soil material - method by sieving and sedimentation. British Standards Institution, UK.

British Standards, 2000. Soil improvers and growing media: BS EN 13039:2000. Determination of organic matter content and ash. British Standards Institution, UK.

493 British Standards, 2007. Soil improvers and growing media: BS EN 13040:2007. Sample
 494 preparation for chemical and physical tests, determination of dry matter content, moisture
 495 content and laboratory compacted bulk density. British Standards Institution, UK.

496 Clark M.L., Roberts D.A, Clark D.B., 2005. Hyperspectral discrimination of tropical rain
 497 forest tree species at leaf to crown scales. *Remote Sensing of Environment*, 96, 375 – 398.

498 Cosh, M.H., Jackson, T.J., Bindlish R., Famiglietti, J.S., Ryu, D., 2005. Calibration of an
 499 impedance probe for estimation of surface soil water content over large regions. *Journal of*
 500 *Hydrology*, 311, 49–58.

501 Dalal, R.C., Henry, R.J., 1986. Simultaneous determination of moisture, organic carbon, and
 502 total nitrogen by near infrared reflectance spectrophotometry. *Soil Science Society of*
 503 *America Journal*, 50, 120-123.

504 Delta-T Devices Ltd., 1999. Theta Probe Soil Moisture Sensor Type ML2x User Manual.
 505 Delta-T Devices, Inc., Cambridge, England.

506 Fleige, H., Horn, R., 2000. Field experiments of the effect of soil compaction on soil
 507 properties, runoff, interflow and erosion. In: Horn, R., et al. (Eds.), *Subsoil Compaction*
 508 *Distribution, Processes and Consequences*. Advance in GeoEcology, vol. 32. CATENA
 509 VERLAG, Reiskirchen, Germany, pp. 258–268.

510 Foley, J.L., Harris, E. 2007. Field calibration of ThetaProbe (ML2x) and ECHO probe (EC-
 511 20) soil water sensors in a Black Vertosol. *Soil Research*, 45(3) 233–236.

512 Gaskin, G.J., J.D. Miller., 1996. Measurement of soil water content using a simplified
 513 impedance measuring technique. *Journal of Agriculture Engineering Research*, 63(2): 153-
 514 160.

515 Günaydin, O. 2009. Estimation of soil compaction parameters by using statistical analyses
 516 and artificial neural networks, *Environmental Geology*, 57, 203-215.

517 Glancey, J.L., Upadhyaya, S.K., Chancellor, W.J., Rumsey, J.W., 1989. An instrumented
518 chisel for the study of soil-tillage dynamics. *Soil & Tillage Research*, 14, 1–24.

519 Grossman, R.B., 1981. Bulk Density: Application, Estimation, and Field Management
520 (second approximation). Nat. Soil Survey Lab., Soil Cons. Survey, Lincoln, NE.

521 Hummel, J.W., Ahmad, I.S., Newman, S.C., Sudduth, K.A., Drummond, S.T., 2004.
522 Simultaneous soil moisture and cone index measurement. *Transaction of the ASAE*, 47,
523 607-618.

524 Jones, S.B., Wraith, J.M., Or, D., 2002. Time domain reflectometry measurement principles
525 and applications. *Hydrol. Process.* 16, 141–153.

526 Kaleita, A.L., Heitman, J.L., Logsdon, S.D., 2005. Field calibration of the theta probe for Des
527 Moines loess soils. *Applied Engineering in Agriculture*, 21(5), 865-870.

528 Khalilmoghadam, B., Afyuni, M., Abbaspour, K.C., Jalalian, A., Dehghani, A.A., Schulin,
529 R., 2009. Estimation of surface shear strength in Zagros region of Iran – a comparison of
530 artificial neural networks and multiple-linear regression models. *Geoderma*, 153, 29–36.

531 Kuang, B., Mahmood, H.S., Quraishi, Z., Hoogmoed, W.B., Mouazen, A.M., van Henten,
532 E.J., 2012. Sensing soil properties in the laboratory, in situ, and on-line: a review. In
533 Donald Sparks, editors: *Advances in Agronomy*, 114, AGRON, UK: Academic Press,
534 155-224.

535 Lobell, D.B., Asner, G.P., 2002. Moisture Effects on Soil Reflectance. *Soil Science Society*
536 *of America Journal*, 66, 722-727.

537 Mahmood, H.S., Hoogmoed, W.B., Van Henten, E.J., 2009. Combined sensor system for
538 mapping soil properties. *Precision agriculture*, 423–430.

539 Martens, H., Naes, T., 1989. *Multivariate Calibration*, 2nd edition. John Wiley & Sons, Ltd.,
540 Chichester, United Kingdom.

541 Miller J.D., Gaskin G.J., 1997. The development and application of the ThetaProbe soil water
542 sensor. MLURI Technical note.

543 Mouazen, A.M., Dumont, K., Maertens, K., Ramon, H., 2003. Two-dimensional prediction of
544 spatial variation in topsoil compaction of a sandy loam field-based on measured horizontal
545 force of compaction sensor, cutting depth and moisture content. *Soil & Tillage Research*,
546 74(1), 91-102.

547 Mouazen, A.M., De Baerdemaeker, J., Ramon, H., 2005. Towards development of on-line
548 soil moisture content sensor using a fibre-type NI R spectrophotometer. *Soil & Tillage*
549 *Research* 80(1–2), 171– 183.

550 Mouazen A.M., Karoui, R., De Baerdemaeker, J., Ramon, H. 2006a. Characterization of soil
551 water content using measured visible and near infrared spectra. *Soil Science Society of*
552 *America Journal* 70, 1295-1302.

553 Mouazen, A.M., De Baerdemaeker, J., Ramon, H. 2006b. Effect of wavelength range on the
554 measurement accuracy of some selected soil properties using visual-near infrared
555 spectroscopy. *Journal of Near Infrared Spectroscopy*, 14(3), 189-199.

556 Mouazen, A.M., Ramon, H., 2006. Development of on-line measurement system of bulk
557 density based on on-line measured draught, depth and soil moisture content. *Soil & Tillage*
558 *Research*, 86(2), 218-229.

559 Mouazen, A.M., Maleki, M.R., De Baerdemaeker, J., Ramon, H., 2007. On-line measurement
560 of some selected soil properties using a VIS-NIR sensor. *Soil & Tillage Research*, 93(1),
561 13-27.

562 Mouazen, A.M., Kuang, B., De Baerdemaeker, J., Ramon, H., 2010. Comparison among
563 principal component, partial least squares and back propagation neural network analyses
564 for accuracy of measurement of selected soil properties with visible and near infrared
565 spectroscopy. *Geoderma*, 158, 23–31.

566 Naderi-Boldaji, M., Alimardani, R., Hemmat, A., Sharifi, A., Keyhani, A., Dolatsha, N.,
567 Keller, T., 2012. Improvement and field testing of a combined horizontal penetrometer for
568 on-the-go measurement of soil water content and mechanical resistance. *Soil and Tillage*
569 *Research*, 123, 1–10.

570 Quraishi, M.Z., Mouazen, A.M., 2013a. A prototype sensor for assessment of soil bulk
571 density. *Soil & Tillage Research*. 10.1016/j.still.2013.07.011.

572 Quraishi, M.Z., Mouazen, A.M. 2013b. Development of a methodology for in situ assessment
573 of topsoil dry bulk density. *Soil & Tillage Research* 126, 229–237.

574 Quraishi, M.Z., Mouazen, A.M. 2013c. Calibration of an on-line sensor for measurement of
575 topsoil bulk density in all soil textures. *Soil & Tillage Research* 126, 219–228.

576 Robinson, D.A., Gardner, C.M.K., Cooper, J.D., 1999. Measurement of relative permittivity
577 in sandy soils using TDR, capacitance and theta probes: comparison, including the effects
578 of bulk soil electrical conductivity. *Journal of Hydrology*, 223, 198-211.

579 Shepherd, K.D., Walsh, M.G., 2002. Development of reflectance spectral libraries for
580 characterization of soil properties. *Soil Science Society of America Journal*, 66, 988-998.

581 Singh, K.K., Colvin, T.S., Erbach, D.C., Mughal, A.Q., 1992. Tilth index: an approach to
582 quantifying soil tilth. *Transactions of ASAE*, 35 (6), 1777–1785.

583 Slaughter, D.C., Pelletier, M.G., Upadhyaya, S.K., 2001. Sensing soil moisture using NIR
584 spectroscopy. *Applied Engineering in Agriculture*, 17, 241–247.

585 Soane B.D., van Ouwerkerk C., 1995. Implications of soil compaction in crop production of
586 the quality of the environment. *Soil & Tillage Research*, 35, 5-22.

587 StatSoft, I., 2011. *STATISTICA* (data analysis software system), 10.

588 Stenberg, B., Viscarra Rossel, R.A., Mouazen, A.M., Wetterlind, J., 2010. Visible and near
589 infrared spectroscopy in soil science. In Donald Sparks, editors: *Advances in Agronomy*,
590 107, AGRON, UK: Academic Press, 163-215.

591 Sun Y., Cheng Q., Lin J., Schulze P., Lammers, Berg A., Meng F., Zeng Q., Li L. 2011.
 592 Energy-based comparison between a dynamic cone penetrometer and a motor-operated
 593 static cone penetrometer. *Soil & Tillage Research*, 115–116, 105–109.

594 Topp, G.C., Davis, J.L., Annan, A.P., 1980. Electromagnetic determination of soil water
 595 content: measuring in coaxial lines. *Water Resources Research*, 16, 574-582.

596 Vrindts, E., Mouazen, A.M., Reyniers, M., Maertens, K., Maleki, M.R., Ramon, H., De
 597 Baerdemaeker, J., 2005. Management zones based on correlation between soil
 598 compaction, yield and crop data. *Biosystems Engineering*, 92(4), 419–428.

599 Viscarra Rossel, R.A., McBratney, A.B., 1998. Laboratory evaluation of a proximal sensing
 600 technique for simultaneous measurement of soil clay and water content. *Geoderma*, 85,
 601 19-39.

602 Viscarra Rossel, R.A., Behrens, T., 2010. Using data mining to model and interpret soil
 603 diffuse reflectance spectra. *Geoderma*, 158(1–2), 46-54.

604 Walker, J.P., Houser, P.R., G.R. Willgoose., 2004. Active microwave remote sensing for soil
 605 moisture measurement: A field evaluation using ERS-2. *Hydrology Processes*, 18(11),
 606 1975-1997.

607 Wijaya, K., Nishimura, Y., Kato, M., Nakagawa, M., 2004. Field estimation of soil dry bulk
 608 density using amplitude domain reflectometry data. *Journal of Japanese Society of Soil*
 609 *Physics*, 97, 3-12.

610 Wuest, S.B., 2009. Correction of bulk density and sampling method biases using soil mass
 611 per unit area, *Soil Science Society of America Journal*, 73(1), 312-316.

Combining frequency domain reflectometry and visible and near infrared spectroscopy for assessment of soil bulk density

Al-Asadi, Raed A.

2014-01-01T00:00:00Z

“NOTICE: this is the author's version of a work that was accepted for publication in Soil and Tillage Research. Changes resulting from the publishing process, such as peer review, editing, corrections, structural formatting, and other quality control mechanisms may not be reflected in this document. Changes may have been made to this work since it was submitted for publication. A definitive version was subsequently published in Soil and Tillage Research, VOL 135, (2014) DOI:10.1016/j.still.2013.09.002”

Raed A. Al-Asadi and Abdul M. Mouazen, Combining frequency domain reflectometry and visible and near infrared spectroscopy for assessment of soil bulk density, Soil and Tillage Research, Volume 135, January 2014, Pages 60–70.

<http://dx.doi.org/10.1016/j.still.2013.09.002>

Downloaded from CERES Research Repository, Cranfield University