

Integration of Torque Blending and Slip Control using Nonlinear Model Predictive Control

M. Sofian Basrah*, Efstathios Siampis, Efstathios Velenis, Dongpu Cao, Stefano Longo
Cranfield University

*E-mail: s.s.basrah@cranfield.ac.uk

Antilock Braking System (ABS) is an important active safety feature in preventing accidents during emergency braking. Electrified vehicles which include both hydraulic and regenerative braking systems provide the opportunity to implement brake torque blending during slip control operation. This study evaluates the design and implementation of a new torque allocation algorithm using a Nonlinear Model Predictive Control (NMPC) strategy that can run in real-time, with results showing that wheel-locking can be prevented while also permitting for energy recuperation.

Topics / Brake, active safety, full-electric vehicles and hybrid electric vehicles

1. INTRODUCTION

Electrified vehicles are equipped with redundant braking actuators, namely hydraulic brakes and a regenerative braking system. This creates the opportunity for research into brake torque blending for Antilock Braking System (ABS) in a hybrid braking system.

Several articles report torque blending algorithms using optimization methods. In [1] an adaptive slip controller is proposed and the brake torque allocation is designed using Control Allocation (CA). In [2] a linear slip controller is designed and a linear Model Predictive Control (MPC) strategy is employed to allocate the brake torque between the two actuators. The cascaded strategy in [2] is replaced with a combined strategy for slip control and torque blending using linear MPC in [3]. Static brake torque allocation by Daisy Chain (DC) which requires less computational effort as compared to optimization methods is proposed and tested on a hardware-in-the-loop simulator in [4].

The problem of integrating slip control and brake torque allocation includes important nonlinearities in both the system dynamics and constraints. The emergence of real time nonlinear solvers make it possible to treat the optimization as a constrained nonlinear problem instead of using linear approximations. To the authors' best knowledge, there is currently no work on integrated slip control and brake torque allocation using Nonlinear Model Predictive Control (NMPC) with real time implementation capability. This work therefore presents a slip control and torque blending strategy incorporated in single NMPC formulation.

2. PREDICTIVE CONTROL STRATEGY

For the NMPC formulation a single-wheel model is employed. Assume that the continuous-time model is

$$\dot{V}_x = \frac{F_x}{m}, \quad (1a)$$

$$\dot{s}_x = -\frac{F_x}{V_x} \left(\frac{R_w^2}{J_w} + \frac{s_x}{m} + \frac{1}{m} \right) + \frac{R_w}{J_w V_x} T_{tot}, \quad (1b)$$

with V_x the wheel's forward velocity, s_x the longitudinal slip, F_x the tyre's longitudinal force, T_{tot} the total torque applied on the wheel and R_w , J_w and m the wheel's radius, moment of inertia and mass respectively. In the above model, F_x is set as a function of s_x through a simplified version of Pacejka's Magic Formula (MF) [5]:

$$F_x = F_z D \sin(C \tan^{-1}(B s_x)), \quad (2)$$

where B , C and D are the MF's factors and F_z the vertical force on the tyre. For our blending strategy, the T_{tot} is the summation of the torque from the electric motor T_e and the torque from the hydraulic brake T_h . Then if the single wheel model (1) is augmented with the trivial equalities $dT_e = T_e^{rate}$ and $dT_h = T_h^{rate}$, the following nonlinear system is obtained

$$\dot{x} = f(x, u), \quad (3)$$

with $x = [V_x \ s_x \ T_e \ T_h]^T$ and $u = [T_e^{rate} \ T_h^{rate}]^T$. Using system (3) the NMPC problem with sampling time T_s and prediction horizon N is

$$\min_u \sum_{k=0}^{N-1} \left\| \begin{bmatrix} V_{xk} - V_x^{ref} \\ s_{xk} - s_x^{ref} \end{bmatrix} \right\|_Q^2 + \|u_k\|_R^2$$

$$\text{s. t. } \begin{aligned} x_0 &= x_{current}, \\ x_{k+1} &= g(x_k, u_k), \quad k = 0, \dots, N-1, \\ \underline{x} &\leq x_k \leq \bar{x}, \\ \underline{u} &\leq u_k \leq \bar{u}, \end{aligned}$$

where we choose to penalize the V_x and s_x errors only from a given reference, along with the control effort in the form of a penalty on the torque rates T_e^{rate} and T_h^{rate} . In this way we do not explicitly set references for the

electric motor torque T_e and the hydraulic brake torque T_h , but rather leave the NMPC find the appropriate values according to the given V_x and s_x references, the torque and torque rate constraints, and the chosen weight matrices $Q > 0$ and $R > 0$.

To solve the NMPC problem online, the Real Time Iteration (RTI) scheme available as part of the ACADO Toolkit [6] is employed, which allows for small computational times as demonstrated in the simulation study of the next section.

Finally, in order to generate the reference wheel speed V_x^{ref} we can use steady-state analysis. Given a longitudinal slip reference s_x^{ref} , a longitudinal force reference can be computed using (2) and from that a constant acceleration target a_x^{ref} from (1a). Then the reference wheel speed is simply given by

$$V_x^{ref} = V_{current} + T_s N a_x^{ref}.$$

3. SIMULATION STUDY

In this section we present preliminary results using the NMPC strategy from section 2 on a single-wheel model in Simulink, with the motor and hydraulic brake modelled as simple 1st order delays (time constants of $\tau_e = 0.03$ and $\tau_h = 0.09$ respectively). The wheel and tyre parameters used can be found in Table 1.

Table 1 Wheel and Tyre Parameters

| | | |
|-------------------------|-------|-----------------------|
| wheel total mass | m | 362.5 kg |
| wheel moment of inertia | J_w | 1.04 kgm ² |
| wheel radius | R_w | 0.3 m |
| MF's stiffness factor | B | 7 |
| MF's shape factor | C | 1.6 |
| MF's peak value | D | 1 |

For the NMPC we set $T_s = 10ms$ and $N = 50$. The rate limits for the motor and the brake are set to $\frac{1000}{0.1}$ Nm/s and $\frac{1000}{0.3}$ Nm/s respectively and the weights in the cost function are chosen such that we penalize large longitudinal slip errors, while also we give priority to the use of the electric motor for the torque delivery: $Q = diag([10, 100000])$, $R = diag([0.08, 0.072])$.

In the presented scenario the wheel is initially free-rolling with initial speed of 30m/s on a dry road ($\mu = 1$) and after 1s a slip target of $s_x = -0.1$ is demanded. As we can see from Fig 1, the NMPC strategy successfully regulates the longitudinal slip (Fig 1(b)) by distributing the T_e and T_h torques (Fig 1(c)), with an obvious preference for the electric motor. It is also worth noting at this point that the commanded torques from the controller are very close to the actual torques as delivered by the actuators, a result of including the torque rate constraints in the NMPC formulation. Finally, as we can see from Fig 1(d), the time to compute the solution using a rather standard laptop (i5-2520M at 2.50Ghz with 8GB of memory) takes around 1ms, which is much lower than the sampling time of 10ms.




Fig. 1 Simulation results

4. SUMMARY & ONGOING WORK

A new unified slip controller and brake torque integration strategy has been proposed in this work using NMPC formulation. Preliminary result shows that real time implementation of NMPC for slip control by different braking actuators can be deployed. Actuator dynamics and constraints have been taken into consideration in the optimization formulation. Ongoing work will include brake torque range limit and validate using high fidelity model.

REFERENCES

- [1] de Castro, R. et al., "Torque blending and wheel slip control in EVs with in-wheel motors," *Vehicle System Dynamics*, vol. 50, no. sup1, pp. 71-94, 2012.
- [2] Satzger, C. et al., "A Model Predictive Control Allocation Approach to Hybrid Braking of Electric Vehicles", *IEEE Intelligent Vehicles Symposium Proceedings*, June 2014.
- [3] Satzger, C. & de Castro, R., "Combined wheel-slip control and torque blending using MPC", *International Conference on Connected Vehicles and Expo*, November 2014.
- [4] Basrah, M. S., et al., "Four wheel torque blending for slip control in a hybrid electric vehicle with a single electric machine", *International Conference on Sustainable Energy Engineering and Application*, October 2015.
- [5] Bakker E. et al., "Tyre modelling for use in vehicle dynamics studies", *SAE Technical Paper*, No. 870421, 1987.
- [6] Houska B. et al., "An Auto-Generated Real-Time Iteration Algorithm for Nonlinear MPC in the Microsecond Range", *Automatica*, Vol. 47, No. 10, 2011, pp. 2279–2285.

2016-09-30

Integration of torque blending and slip control using nonlinear model predictive control

Basrah, M. Sofian

Unknown

M. Sofian Basrah, Efstathios Siampis, Efstathios Velenis, Dongpu Cao and Stefano Longo. Integration of torque blending and slip control using nonlinear model predictive control. In: 13th International Symposium on Advanced Vehicle Control, AVEC'16, 13-16 September 2016, Munich, Germany, pp.585-592

<https://doi.org/10.1201/9781315265285>

Downloaded from Cranfield Library Services E-Repository