



GHGT-12

Engineering Scale-Up Challenges, and effects of SO₂ on the Calcium Looping Cycle for Post Combustion CO₂ Capture

Alissa Cotton^a, Kumar Patchigolla^{b*}, John E. Oakey^b

^aGB Shell Research Limited, 2 York Road, London, SE1 7NA

^bInstitute for Energy and Resource Technology, Cranfield University, Cranfield, Beds, MK43 0AL

Abstract

Engineering scale-up challenges, and potential effects of SO₂ on the calcium looping cycle for post combustion CO₂ capture have been investigated in Cranfield University's pilot scale reactor (25 kW_{th}). Following reactor and process modifications, close to 80% capture was achieved. SO₂ was found to have a detrimental effect on the calcium looping cycle in both batch and continuous cyclic tests, although the presence of steam from natural gas-fired burners was found to have a positive effect on maintaining capture capacity of the sorbent.

© 2014 The Authors. Published by Elsevier Ltd. This is an open access article under the CC BY-NC-ND license (<http://creativecommons.org/licenses/by-nc-nd/3.0/>).

Peer-review under responsibility of the Organizing Committee of GHGT-12

Keywords: CO₂ Capture; Calcium looping; Scale-up; SO₂; Post combustion

1. Introduction

Calcium looping cycle technology has been identified as a promising carbon capture technology, in particular from coal-derived flue gas, since first being proposed by Shimuzu et al. [1]. The process has been researched extensively at bench scale, but it is widely acknowledged that further work is required prior to industrial implementation. The pilot scale calcium looping facility at Cranfield is the largest of its kind in the UK (as part of

* Corresponding author. Tel.: +44(0)1234 750111;
E-mail address: k.patchigolla@cranfield.ac.uk

the Pilot Advanced Capture Technologies; www.PACT.ac.uk), and is considered capable of achieving beyond 80 % capture with improved components in place. This is considered important in order to show the capability of the technology and in turn build a demand for it, as the UK moves towards a low carbon energy scenario incorporating CO₂ capture. This study shares the lessons learnt and improvements made in operating and developing the Ca looping cycle at the pilot-scale.

Figure 1 outlines the calcium looping process, which comprises calcination of limestone in a calciner reactor to produce CaO sorbent, which is then transferred to a second reactor, where CaO reacts with flue-gas derived CO₂ to form CaCO₃ via the carbonation process. The CaCO₃ is then transferred back to calciner for where it is thermally decomposed, releasing CO₂ for compression, transport and storage, and reproducing CaO for repeated cycles of CO₂ capture. The process encompasses gas-solid fluidised bed technology.

Sulphur is naturally present in coal, primarily forming SO₂ on combustion, which in turn during the sulphation reaction, reacts with CaO to form CaSO₄ and CaS, the production ratio of which is temperature dependent [2]. Sulphation causes blocking of larger CaO pores formed during cyclic carbonation-calcination, which could otherwise react with CO₂ to form CaCO₃. Research at the bench scale [3] [4] [5] has shown that SO₂ and the resulting CaSO₄ formation contribute to the deactivation of CaO. Effects of SO₂ on the calcium looping cycle have therefore been investigated as part of this work.




Figure 1 Calcium looping cycle, comprising calcination of CaCO₃ in the calciner to produce a high-purity CO₂ stream for transport and storage, after which CaO is transferred to the carbonator for CO₂ capture, producing CaCO₃ which is then cycled back to the calciner.

2. Methodology

Experiments were undertaken in a 25kW_{th} pilot-scale CO₂ capture rig comprising an entrained flow bed carbonator reactor, and a bubbling fluidised bed calciner reactor. The carbonator is of 0.1 m diameter, and 4.3 m length, and the fluidising gases are provided by a natural gas-fuelled air burner, the fuel gas in which provides the fluidised bed. The calciner is of 0.165m diameter, and of 1.2m length, and is a natural gas oxy-fuel combustor. Both reactors and associated fittings are made of 310 stainless steel.

A view port is located at the top of the calciner from where the reactor is filled with solids prior to testing, and the calciner also has a drain to allow sampling of solids during and after testing. Two cyclones are present in series at the carbonator exhaust to ensure efficient particulate removal from the flue gases, and therefore prevent particulate

emissions to the environment. The carbonator and calciner are connected by two loop seals, comprising an upper loop seal (ULS) and a lower loop seal (LLS), allowing controlled solids transfer, and thus regulating the solids flux from the calciner to the carbonator, and vice versa. Following entrainment of solids in the carbonator, solids are separated from the gas stream by the first cyclone, allowing exhaust gases to exit the system, and solids to continue in a looping mode. The ULS is present downstream of the cyclone exit standpipe, to allow controlled transfer of solids to the calciner. The LLS is located towards the bottom of the calciner, allowing controlled transfer of solids from the calciner to the carbonator. Both loop seals must be fluidised in order for the solids to be transferred. Therefore, each loop seal has two gas distributor nozzles in the ‘entry’ half of the loop seal, and two distributor nozzles in the ‘exit’ side of the loop seal.

Trace heating is present the length of the carbonator and calciner and is required to ensure the desired temperature for the initial start-up of the system, to maintain the required operating temperatures, and also to reduce condensation effects. The carbonator has a total of eight trace heating elements whilst the calciner has a total of four heating elements along its length. Each heating element is of 1 kW capacity and can be independently controlled, thus allowing different temperatures to be set to meet the required thermal conditions and to maintain a constant temperature along each reactor length. Typically, each carbonator heating element was set to approximately 600°C, whilst each calciner heated element was set to approximately 900°C.

In order to observe any morphological changes which may have occurred to the limestone sorbent as a result of the calcium-looping process, a number of chemical analytical techniques have been used. Energy Dispersive X-Ray Spectroscopy (EDS) was used to confirm the elemental composition of each sample. Particle Size Distribution (PSD) analysis was carried out prior to and after testing using a Malvern Mastersizer 2000. Brunauer-Emmett-Teller (BET) surface area analysis and Barrett-Joyner-Halenda (BJH) (Tristar 3000) pore size and volume analysis were also carried out to determine any changes in sorbent morphology as a result of testing

3. Results and Discussion

Close to 80 % CO₂ capture has been achieved in the pilot scale reactor (Figure 2) through experimental development.




Figure 2. CO₂ capture achieved following reactor and process modifications

This development has comprised a number of process and reactor modifications, including, but not limited to, optimisation of reactor temperatures, enhanced heating of the ‘loop seal’ non-mechanical transfer valves through the

addition of heated elements, and also addition of pneumatic vibration components on loop seals to encourage solids transfer .

Lower carbonator temperatures of ~600-650 °C have previously been identified as being beneficial at the pilot scale due to the presence of temperature gradient across a fluidised bed [6], and this has been confirmed in this study. Decreasing the carbonation temperature by approximately 50°C had a positive effect on increasing % capture in the reactor, from an optimum capture of ~ 60 % for a carbonator temperature of 650-700°C, to ~ 70 % capture for a carbonator temperature of 600-650°C. This is primarily due to the effect of partial pressure of CO₂ on the carbonation reaction. By reducing the temperature in the carbonator, the partial pressure required for carbonation was also reduced, thereby driving forward the formation of CaCO₃ from CaO and CO₂.

The importance of sufficiently high temperatures above 420°C [7] in transfer lines between the reactors, including loop seals and associated standpipes, has been proven in this study as a mitigation measure against Ca(OH)₂ formation, to minimise its associate negative attributes on the Ca looping cycle, to thereby improve the capture %.

With particular regard to pilot scale testing, the use of efficient gas distributors (bubble caps in this case) is considered to hold potential benefits over conventional distributors such as those used in this study. It is considered that the use of bubble caps may reduce weeping of solids from the reactor the plenum, particularly when a pressure drop is experienced in the system, and also to prevent blockage of gas distributors which can lead to reduced gas flows and in turn reduced fluidization and CO₂ capture.

3.1. Effects of SO₂ – Batch tests

The effect of SO₂ has been investigated at the pilot scale, and Figure 3 shows results from single column batch experiments. Increasing SO₂ concentrations appears to decrease % CO₂ capture, which is likely to be caused by the well-documented detrimental effect of SO₂ on CO₂ capture, due to the formation of CaSO₄. CaSO₄ has a molar volume of 46 cm³/mol, compared to a molar volume of 37 cm³/mol for CaCO₃ [8], and therefore acts to block pores and impede CO₂ capture. This is supported by Figure 4, which shows the average pore diameter of sorbent sampled from the reactor after each test for 0, 1000 and 2000 ppm SO₂, and identifies that increasing SO₂ concentration reduces the average pore diameter, from 55 nm to 28 to 10 nm for 0, 1000 and 2000 ppm respectively. In general, reactions are limited by pore size, as well as by pore surface area and pore distribution. Pore surface area can be considered the area where reactions can take place, while pore volume is the space in which products can grow. Pore diameter can be defined as the space limitation in a single pore [8].

For 0 ppm SO₂, the % CO₂ capture remained close to 100 % for the longest period of time before beginning to decrease. However, for 1000 ppm SO₂, this remained at a high level (above approximately 90 %) for the longest period of time before beginning to decrease. Further, the % capture at the end of the test was approximately 36 %, 2 % and 9 % for 0, 1000, and 2000 ppm SO₂ respectively. The fact that the 1000 ppm SO₂ test had a lower final capture % than the 2000 ppm SO₂ test is unexpected, as given the well-documented detrimental effects of SO₂ on carbonation, it would be expected that the 2000 ppm test had the lowest final % capture. A reason for this outcome however could be the positive effect that SO₂ may have in decreasing effects of attrition [3]. This is supported by Figure 5 which shows that sorbent from the 0 ppm test experienced the greatest decrease in particle diameter, whilst the sorbent tested with 1000 ppm SO₂ had the largest mean particle diameter and volume when compared with sorbent tested in 0 and 2000 ppm SO₂, suggesting that 1000 ppm SO₂ represents a compromise between pore blockage and attrition. Jia *et al.* [9] too found that ‘light’ sulphation of limestone in SO₂ concentration of 1800 ppm resulted in reduced material loss as a result of attrition.




Figure 3 Effect of increasing SO₂ concentration on % CO₂ capture.




Figure 4 BJH analysis showing average pore diameter of sorbent sampled from the reactor after each tests, for 0, 1000 and 2000 ppm SO₂.




Figure 5 PSD analysis of sorbent sampled from the reactor after each tests, for 0, 1000 and 2000 ppm SO_2 .

EDS analysis (Figure 6) of sorbent after each test suggests reduced carbonation with increasing SO_2 concentration, implied by decreasing weight % of C and O, and increasing weight % of S. However, the weight % of Ca does not increase linearly, as would be expected for reduced carbonation, and instead decreases from 40.5 % at 0 ppm, to 36.7 % 1000 ppm, before then rising to 41 % for 2000 ppm SO_2 . This again could be indicative of 1000 ppm producing some form of compromise between pore blockage and reduced attrition effects, or may be attributed to an anomalous reading obtained from the EDS analysis.




Figure 6 EDS analysis of sorbent exposed to increasing SO_2 concentrations in single column experiments.

3.2. Effects of SO_2 –Continuous Cycling tests

The effect of increasing SO_2 concentration on the CO_2 capture efficiency of the calcium-looping cycle was also investigated in continuous cycling tests, which identified that increasing SO_2 concentration appears to decrease the % capture efficiency (Figure 7). This is likely due to pore blockage as a result of CaSO_4 formation. This is in

accordance with the majority of work available in the literature [5] [10]. However, it is apparent that the % capture for each test shown does not appear to decrease over time with increasing carbonation/calcination cycles, as would be expected from typical CO₂ capture curves. The reason for this may be due to the quantities of steam produced by the carbonator's air-fired burner, and the calciner's oxy-fired burner, at 87 l/min and 108 l/min H₂O in the carbonator and calciner respectively. The effects of additional steam on % CO₂ capture in the calcium-looping cycle have been investigated, and it is apparent from this work and research available in the literature that addition of steam during carbonation/ calcination improves % CO₂ capture due to the acceleration and enhancement of the fast-diffusion process in carbonation.




Figure 7 Effect of SO₂ concentration on % CO₂ capture during pilot scale calcium-looping.

With further regard to the reduction in CO₂ % capture proposed due to pore blockage, Figure 8 shows the results of BET analysis for sorbent sampled from the reactor after each test. It identifies that the sorbent tested in 2000 ppm and 1000 ppm SO₂ has a smaller pore volume than that tested without, implying pore blockage had occurred. The pore diameter for sorbents from all three test scenarios was very similar, with sorbent from 0 and 1000 ppm SO₂ addition tests showing slightly smaller diameters, the smallest of which was approximately 2 nm and can be considered small pores (<6 nm), compared to a close value of 7nm for the 2000 ppm SO₂ test. The pronounced peak in pore volume at a diameter of ~3nm for the 0 ppm test and also to a lesser extent for the 1000 ppm test is interesting. It suggests that the small pores that contribute to pore volume and thus important for CO₂ capture, are filled with increasing SO₂ concentration, and thus in this case it is both the small and large pores that are active in reducing CO₂ capture capacity. This is in contrast to thermogravimetric analysis (TGA) work carried out by Chen *et al.* [8] who suggested that decay in activity is largely due to changes in large pores, and also Gullet and Bruce [11] (from Sun *et al.* [5]) who suggested sulphation fills pores of 10-60 nm or larger. In the carbonator, where CaO particles are transferred in order to be carbonated, sulphation (i.e. sulphation of CaO) is more likely to occur than direct sulphation (sulphation of CaCO₃) because of the larger surface area of CaO. The reason for this filling of small pores may be due to diffusion of CO₂ through the CaSO₄ layer, due to its smaller molecular volume when compared to SO₂, thereby filling smaller pores, which in the absence of SO₂ is not 'necessary' for it to do. This may be more pronounced at pilot scale than bench scale because of the larger area available over which reactions can take place in a fluidised bed, compared to a fixed bed in a TGA.




Figure 8 BET analysis of sorbent taken from reactor after testing with increasing SO_2 concentrations.

With regards to attrition, Figure 9 shows the results of sorbent PSD analysis after testing, showing very similar PSD for all 3 tests. In this case the sorbent from the 2000 ppm SO_2 test shows a slightly higher extent of attrition than the 1000 ppm, and in turn the 0 ppm test. This is in contrast to single column tests with SO_2 which showed slight a decrease in attrition with SO_2 present. The difference may be due to the looping cycle process, during which particles are subjected to other forces, including gravitational, drag, buoyancy and pressure forces [12], which in single column tests they would not experience, including the abrasive bed, and the reactor walls. This in turn may result in a weaker CaSO_4 surface layer, and / or removal of said layer. Similar results whereby increasing SO_2 caused a slight increase in attrition were found by Coppola *et al.* [10] in bench scale, batch tests with 1800 ppm SO_2 .




Figure 9 PSD analysis of sorbent sampled from reactor after testing with increasing concentrations of SO_2 .

4. Conclusions

CO_2 capture tests have been carried out in a pilot scale reactor employing the calcium looping cycle in continuous mode. A maximum CO_2 capture % of close to 80% has been achieved in this reactor, following a number of process and reactor modifications. It is considered that a higher % capture could be achieved with further modifications to

improve the solids inventory, solids circulation rate and residence time of solids in the reactor, as well as improvements to the burner reliability. The effects of SO₂ have been investigated at the pilot scale in both batch and continuous experiments, and it was found, in accordance with work available in the literature, that SO₂ has a detrimental effect on CO₂ capture. This is supported by PSD, BET, and EDS analysis of sorbent samples subsequent to testing. The large water content present in the reactor from the use of an air and oxy-fired burner seems to have a positive effect in maintaining the CO₂ capture % achieved by the sorbent.

Acknowledgements

The authors wish to acknowledge M. Roskilly for his help and support with the experimental work. In addition, the authors wish to acknowledge the UK Engineering and Physical Sciences Research Council (EPSRC) for financial support of this research programme (grant reference: EP/G062374/1 – Joint UK/China Hydrogen Production Network).

References

- [1] Shimizu, T., Hiramata, T., Hosoda, H., Kitano, K., Inagaki, M. and Tejima, K. (1999), "A Twin Fluid-Bed Reactor for Removal of CO₂ from Combustion Processes", *Chemical Engineering Research and Design* 77, 1, 62-68.
- [2] Muñoz-Guillena, M. J., Linares-Solano, A. and Salinas-Martínez de Lecea, C. (1994), "A study of CaO-SO₂ interaction", *Applied Surface Science* 81, 4, 409-415.
- [3] Grasa, G. S., Alonso, M. and Abanades, J. C. (2008), "Sulphation of CaO Particles in a Carbonation/Calcination Loop to Capture CO₂", *Industrial and Engineering Chemistry Research* 47, 5, 1630-1635.
- [4] Weimer, T., Berger, R., Hawthorne, C. and Abanades, J. C. (2008), "Lime enhanced gasification of solid fuels: Examination of a process for simultaneous hydrogen production and CO₂ capture", *Fuel* 87, 8-9, 1678-1686.
- [5] Sun, P., Grace, J. R., Lim, C. J. and Anthony, E. J. (2007), "The effect of CaO sintering on cyclic CO₂ capture in energy systems", *AICHE Journal* 53, 9, 2432-2442.
- [6] Lu, D. Y., Hughes, R. W., Anthony, E. J., 2008. Ca-based sorbent looping combustion for CO₂ capture in pilot-scale dual fluidized beds. *Fuel Processing Technology* 89 (12): 1386- 1395.
- [7] Anthony, E. J., Bulewicz, E. M. and Jia, L. (2007), "Reactivation of limestone sorbents in FBC for SO₂ capture", *Progress in Energy and Combustion Science*, 33, 2, 171-210.
- [8] Chen, H., Zhao, Z., Huang, X., Patchigolla, K., Cotton, A. and Oakey, J. E. (2012), "Novel optimised process for utilisation of CaO-based sorbent for capturing CO₂ and SO₂ sequentially", *Energy and Fuels* 26, 9, 5596-5603.
- [9] Jia, L., Hughes, R., Lu, D., Anthony, E. J. and Lau, I. (2007), "Attrition of calcining limestones in circulating fluidized-bed systems", *Industrial and Engineering Chemistry Research*, 46, 15, 5199-5209.
- [10] Coppola, A., Montagnaro, F., Salatino, P., Scala, F. and Scala, F. (2012), "Fluidized bed calcium looping: The effect of SO₂ on sorbent attrition and CO₂ capture capacity", *Chemical Engineering Journal* 207-208, 445-449.
- [11] Gullet, B. K. and Bruce, K. R. (1987), "Pore distribution changes of calcium-based sorbents reacting with sulphur dioxide", *AICHE Journal* 33, 10, 1719-1726.
- [12] The University of Texas at Austin. (The University of Texas at Austin), Unit operations ChE 354: Fixed and fluidised beds (unpublished Lecture), US.